

FIG. 1A





FIG. 1B






FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7



Appl. No. To be Assigned; Filed: January 21, 2004
 Dkt. No. 1875.0960002; Group Art Unit: To be Assigned
 Inventor: Arya Reza Behzad; Tel: 202/371-2600
 Title: Adjustable Bandwidth High Pass Filter for Large Input
 Signal, Low Supply Voltage Applications

FIG. 8




FIG. 9
 (PRIOR ART)




FIG. 10
 (PRIOR ART)







FIG. 11**FIG. 12**

FIG. 13




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20



[illegible][illegible]

FIG. 23




FIG. 24




FIG. 25





FIG. 26



SWITCH SIZING:
 N: $w=1.8\mu$, $L=0.25\mu$, $m=2$
 P: $w=2\mu$, $L=0.25\mu$, $m=8$

FIG. 27




FIG. 28





FIG. 29



Appl. No. To be Assigned; Filed: January 21, 2004
 Dkt. No. 1875.0960002; Group Art Unit: To be Assigned
 Inventor: Arya Reza Behzad; Tel: 202/371-2600
 Title: Adjustable Bandwidth High Pass Filter for Large Input
 Signal, Low Supply Voltage Applications





FIG. 31

PROGRAMMABLE GAIN AMPLIFIER (PGA)



Appl. No. To be Assigned; Filed: January 21, 2004
Dkt. No. 1875.0960002; Group Art Unit: To be Assigned
Inventor: Arya Reza Behzad; Tel: 202/371-2600
Title: Adjustable Bandwidth High Pass Filter for Large Input
Signal, Low Supply Voltage Applications

FIG. 32

COARSE AND FINE PGA GAIN SETTINGS





FIG. 33
 AGC BLOCK DIAGRAM



Appl. No. To be Assigned; Filed: January 21, 2004
 Dkt. No. 1875.0960002; Group Art Unit: To be Assigned
 Inventor: Arya Reza Behzad; Tel: 202/371-2600
 Title: Adjustable Bandwidth High Pass Filter for Large Input
 Signal, Low Supply Voltage Applications

FIG. 34

PEAK TO RMS RATIOS FOR 100Base-TX AND GIGABIT

CABLE LENGTH [m]	100Base TX	GIGABIT, 100 OHM	GIGABIT, 85 OHM	GIGABIT, 115 OHM
0	3.691281	4.193192	4.193192	4.193192
20	3.806628	4.501316	4.362110	4.291369
40	3.877284	4.528136	4.457336	4.429949
60	3.894216	4.733644	4.695307	4.646305
80	4.055372	4.878569	4.847844	4.810019
100	4.225522	4.983545	4.991296	4.968900
120	4.357733	5.134131	5.194401	5.154263
140	4.556012	5.266919	5.380943	5.366309
160	4.764462	-	-	-

$$\begin{aligned} \text{TARGET } E\{|x|\} &= \text{A/D CLIPPING LEVEL} \times (E\{|x|\}) / (\text{PEAK/RMS}) \\ &= 127 \times 0.7979 / 5.2 = 20 \end{aligned}$$